# DESIGN PHASE, I: Object-Oriented Design

This part is based upon chapter 6 of Schach's "Practical Software Engineering".

# Objectives:

- Appreciate that design is an essential part of the software life cycle
- Realize why a function should perform one task
- Discover what an object is
- Learn how to design a product in terms of objects
- Recognize the critical importance of reusability

# WHY DESIGN?

Why one have to design a product? There are two reasons:

- 1. Cost of Development
- 2. Cost of Maintenance

As to the cost of development:

• If there is no design one uses essentially the buildand-fix model, since until now one has only specified what has to be done, but not how that is to be done.

217 218

#### As to the cost of maintenance:

- It is inevitable that a product will undergo changes.
   Therefore the real issue is how easy it is to make changes.
- If a product is well-designed by using objects this has **two** results:
  - 1. It is easy to determine **what** has to be changed. This is because, using information hiding principles, any part likely to be changed (see transparencies 208-212) has been hidden from other modules.
  - 2. these changes can be localized using the same principles of OO design.

For these two reasons (costs of development and of maintenance) it is foolhardy to build a product without designing it.

So: HOW DOES ONE DESIGN A PRODUCT?

# **OBJECT-ORIENTED DESIGN**

The superior use of objects in design has been documented on transparencies 173-216.

In the context of the team project "Chocoholics Anonymous", it is important to realize this project is implemented within C. Consequently "inheritance" and "information hiding" is not fully supported, and, for the duration of the project, we adhere to the following principles and definitions:

The fundamental building blocks of a project are *objects*; these are compilation units consisting of a data structure together with all operations that are performed on that data structure.

220

Object-Oriented Design (OOD) is essentially a technique that extracts the objects and results is a design that is based on these objects. It is a four-step process:

- **STEP 1** Define the problem as concisely as possible.
- **STEP 2** Develop an informal strategy a general sequence of steps for satisfying the specification document subject to the constraints.
- **STEP 3** Identify the objects; that is the data structures and the operations to be applied to those data structures.
- STEP 4 Perform the detailed design.

Next the OOD is applied to the C-CC case study.

221 222

- **STEP 3** Formalize the strategy. Identify the objects. That is: the data structures and the operations to be performed on them.
  - This is usually done in OOD by identifying the nouns in the informal strategy, excluding those that lie outside the problem boundary and then using the remainder as the basis for the data structure of each object.
  - Then **the verbs are identified**, and used as the basis for the operations of these objects. This usually requires **stepwise refinement**.
  - Finally, as last step in **formalizing the strategy** and as a preparation upon detailed design, a top level design is produced featuring the components in term of which the design of the product will be structured.

So first the **NOUNS** in the informal strategy above are identified:

C-CC has a SET of SHOPS organized into REGIONS. At the end of every MONTH, REPORTS have to be produced for each SHOP and each REGION, and for the CORPORATION as a WHOLE. The REPORTS reflect whether or not sales OBJECTIVES have been met.

Six of the nouns in the example can be discarded for the moment:

- SET, because it will be implemented
- MONTH, WHOLE, OBJECTIVE, because they are abstract nouns, which are within our example unlikely to correspond with an object
- C-CC, CORPORATION, because they lie outside of the problem boundary.

OOD CASE STUDY

**STEP 1** Concise problem description. A definition of the problem in, preferably, one sentence:

Monthly effectiveness reports must be reproduced for C-CC shops.

**STEP 2** *Informal strategy.* Describe the strategy for solving the problem is a single paragraph:

C-CC has a set of shops organized into regions. At the end of every month, reports have to be produced for each shop and each region, and for the corporation as a whole. The reports reflect whether or not sales objectives have been met.

223

Consequently, three candidates for objects remain:

# • REGION, REPORT, SHOP

Of the verbs, only **produce** and **meet objective** relate to these candidates.

This results in our **first refinement** of the Object-operation table:

Object	Operations
REGION	
REPORT	produce
SHOP	meet objective

Figure 6.6 Object-operations table: first refinement.

In view of our definition of data stores in the Specification document case study, see transparencies 162-163 and 151-156, this leads to the **second refinement:** 

Object	Operations
REGION	read region_record
REPORT	produce
SHOP	read shop_record
	evaluate sales_objective

Figure 6.7 Object-operations table: second refinement.

225

Next, in the context of the requirements phase, it is decided that "evaluate sales\_objective" is done by the vice-president for sales, and consequently that the reflection of this upon the product leads to identification of produce a REPORT and of evaluate sales\_objective, making object REPORT redundant.

This leads in view of the Dataflow diagram for the C-CC corporation, transparency 143, to fig. 6.8 below as **third refinement**.

Object	Data Structure	Operations
REGION	region_record	read region_record write region_record delete region_record generate region_report generate
SHOP	shop_record	vice-president_report  read shop_record  write shop_record  delete shop_record  generate shop_report

Figure 6.8 Object-operations table: third refinement.

Now the complete top-level OOD for the C-CC management-by-objectives product is produced in fig. 6.9; this figure reflects the operations upon SHOP and REGION data occurring in the DFD for the C-CC product, cfr transparency 143.




Figure 6.9 OOD of C-CC management-by-objectives project.

228

227

The refinement of these components belongs to **STEP 4** of the OOD and covers the detailed design discussed below.

REUSABILITY

**Reusability** is an increasingly important aspect of software engineering because it reduces development time, and, more importantly, decreases the cost of maintenance:

- 1. Reused functions contain fewer faults
- 2. Maintenance programmers tend to be familiar with reused functions, and consequently:
- 3. it is easier for the maintenance programmer to understand the product as a whole, as a consequence of their familiarity with these functions, and:
- 4. Reused functions tend to generate less regression faults.

229 230

In practise whole chunks of specification documents and manuals can be reused. Studies have shown that:

achieving a 40% level of reusability is an attainable goal.

# Summary:

- Promoting reusability decreases the very high, and still increasing, cost of software; however, its real savings occur in the maintenance phase.
- If all the products developed by an organization consist as far as possible of standard products, maintenance will no longer be a nightmare consuming two-thirds of the time and effort invested in a software product.

**(TERM PROJECT)** Perform the OOD of the ChocAn product.